



Veterinary Digital Imaging System



Simple, Affordable, Reliable



X-Ray Tube:
 Rotating anode 3000 rpm, 0.6/1.2
 Focal Spot
 Filament current safety and automatic control
 Over current and over voltage protection)
 X-ray tube load protection
 Reporting errors or malfunction



DR Flat Panel Detector: Vivix 17"x17"
 Gadolinium Scintillator (Csi also available)
 3.5lp/mm Spatial resolution
 14 Bit A/D 16 Bit Digital Output
 16,384 shades of gray
 Integration to Generator through Vxvue Software.



High Frequency Generator
 Selection of mA in 7 values from 80 to 400mA
 Selection of exposure time from .003 to 2 sec.
 kV from 40 to 125 kV
 Generator inside table small foot print
 Power Supply: 110 V, 20 amps, or 230/240V, 7.5 amps, single phase service

M3 Vet System also includes:
 Acquisition PC: Windows 7Pro
 1TB Raid 1 Configured Harddrives
 Intel I5 Processor
 2mp High Resolution 22" Monitor Touch Screen
 QxLink PACS with Unlimited Viewing Licenses

Warranty:
 Table and Generator 5 years
 3 years DR Panel
 1 year Computer Hardware
 1 year Monitor