



## Veterinary Digital Imaging System



Simple, Affordable, Reliable



X-Ray Tube:  
 Rotating anode 3000 rpm, 0.6/1.2  
 Focal Spot  
 Filament current safety and automatic control  
 Over current and over voltage protection  
 X-ray tube load protection  
 Reporting errors or malfunction



DR Flat Panel Detector: Vivix 17"x17"  
 Gadolinium Scintillator (Csi also available)  
 3.5lp/mm Spacial resolution  
 14 Bit A/D 16 Bit Digital Output  
 16,384 shades of gray  
 Integration to Generator through Vxvue Software.



High Frequency Generator  
 Selection of mA in 7 values from 80 to 400mA  
 Selection of exposure time from .003 to 2 sec.  
 kV from 40 to 125 kV  
 Generator inside table small foot print  
 Power Supply: 110 V, 20 amps, or 230/240V, 7.5 amps, single phase service

M3 Vet System also includes:

Acquisition PC: Windows 7Pro  
 1TB Raid 1 Configured Harddrives  
 Intel I5 Processor  
 2mp High Resolution 22" Monitor Touch Screen  
 QxLink PACS with Unlimited Viewing Licenses

Warranty:

Table and Generator 5 years  
 3 years DR Panel  
 1 year Computer Hardware  
 1 year Monitor